



**WACKER
NEUSON**
all it takes!

PSA2 800, 230 V

5000620450

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> [PSA2 800, 230 V](#)



PSA2 800, 230 V

Material number 5000620450

Electric, single phase submersible trash pump for dewatering, with automatic switch, safety plug and Storz coupling.

Product details

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Silicon carbide-faced double mechanical seals run in isolated oil filled cavity
- Automatic switch
- Heavy-duty strain relief power cord

Comes with

- Pump
- Operator's manual

Technical specifications

PSA2 800, 230 V

ELECTRICAL SYSTEM

Cable cross-section	1,0 mm ²
Length Cable	10,00 m

MECHANICAL - OUTPUT DETAILS

Solid diameter max.	6,0 mm
Delivery height max.	5,0 m
Flow rate max.	310 l/min

ELECTRICAL - OUTPUT DETAILS

Nominal voltage	230 V
Nominal frequency	50 Hz
Starting current full load	5,0 A
Starting current Idle running	12,3 A
Phase	1 ~

MECHANICAL DETAILS

Length	223 mm
Width	187 mm
Height	341 mm
Operating weight	13,8 kg
Intake-/Pressure socket-dia.	50 mm

MOTOR

Nominal speed

2.730 1/min

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE